eSynC-P2UE-F Specification Sheet

Fast-Charging SimulCharge™, PoE, Ethernet, 2 x USB Adapter with RBM Technology for USB-C Mobile Devices

The eSynC-P2UE-F is a fast-charging SimulCharge[™] adapter designed for use with select USB-C mobile devices. It features simultaneous charging and access to data, Power over Ethernet (PoE), wired Ethernet connectivity and 2 USB-A ports for connecting USB peripherals. PoE allows the adapter to be placed up to 328 ft (100 m) away from the PoE-capable network switch or injector. It can either fast charge the mobile device at 9 volts or provide standard charging at 5 volts. The eSynC-P2UE-F also features Network Recovery & Battery Modulation (RBM) technology. Battery Modulation protects the mobile device's battery from overcharging, while Network Recovery can recover a dropped wired Ethernet connection. The LAVA Tablet Manager (LTM) app must be installed on the mobile device for the adapter to work properly.

FEATURES

- USB Host operation while charging (SimulCharge[™])
- · Power over Ethernet (Class 0)
- Fast Charging
- · Wired networking (10/100 Ethernet) support
- · 2 x USB-A ports
- · Battery Modulation for mobile device longevity

- · Network Recovery
- · Screen Brightness Management
- Support for installations running 24/7
- No mobile device rooting required
- LAVA Limited Warranty

SYSTEM REQUIREMENTS

· Mobile devices: Please refer to the published compatibility list

· Installation of LTM app

POWER INPUT

- · Power over Ethernet (13W maximum)
- · Appears as a Class 0 PoE Device

POWER OUTPUT (TO MOBILE DEVICE)

9V at 1.1A (fast charging)

· 5V at 2A

POWER SUPPLY

· PoE-Capable Network Switch or Power Injector (up to 13W)

PORTS/CONNECTORS

- $\cdot~1$ x RJ45 10/100 Ethernet port (for PoE & LAN)
- · 2 x USB-A ports (for USB 2.0 accessories)

· 1 x USB-C port (mobile device connection)

INDICATOR LEDS

- · 1 x Charge Status indicator LED
- · 1 x Device Link indicator LED

- · 1 x Link / Activity indicator LED (On Ethernet Port)
- · 1 x USB Activity indicator LED (On Ethernet Port)

CABLES

 \cdot 1 x USB-C to USB-C cable (up to 5ft/1.5m)

Note: The cable is not included. However, it may be purchased from LAVA.

MEASUREMENTS

- · Depth: 4.96 inches (126 mm)
- · Width: 3.78 inches (96 mm)

- Height: 1.69 inches (43 mm) with standoffs
- · Weight: 4.4 oz (125 g)





