

eSynC-1U *Specification Sheet*

SimulCharge™, 1 x USB Adapter with RBM Technology for USB-C Mobile Devices

The eSynC-1U is a SimulCharge™ adapter designed for use with select USB-C mobile devices. It features simultaneous charging and access to data and 1 USB-A port for connecting a USB peripheral. The eSynC-1U also features RBM technology's Battery Modulation, which protects the mobile device's battery from overcharging. The LAVA Tablet Manager (LTM) app must be installed on the mobile device for the adapter to work properly.

FEATURES

- USB Host operation while charging (SimulCharge™)
- 1 x USB-A port
- Battery Modulation for mobile device longevity
- Screen Brightness Management
- Support for installations running 24/7
- No mobile device rooting required
- LAVA Limited Warranty

SYSTEM REQUIREMENTS

- Mobile Device: Please refer to the published compatibility list.
- Installation of LTM app

POWER INPUT & OUTPUT

- 5V at 2A

POWER SUPPLY

- USB charger/power supply with a USB-C connector, such as the power supply provided with the mobile device. Any regulated 5-volt power supply capable of at least 2 amperes can be used.

PORTS/CONNECTORS

- 1 x USB-A port (for USB 2.0 accessory)
- 2 x USB-C ports (power input and to mobile device ports)

INDICATOR LEDS

- 1 x Charge Status indicator LED
- 1 x Device Link indicator LED
- 1 x USB connect indicator LED

CABLES

- 1 x USB-C to USB-C cable (up to 5ft/1.5m)
Note: The cable is not included. However, it may be purchased from LAVA.

MEASUREMENTS

- Depth: 3.3 inches (84 mm)
- Width: 3.8 inches (97 mm)
- Height: 1.7 inches (44 mm) – with standoffs
- Weight: 4.0 oz (113 g)